

Multi-Sports Pavilion

By: Nari Kim, Dezhong Wang, Ruomeng Li,
Christopher Olivarez, Brendon R. Bangert



Introduction | Context

- Madrid, Spain
- University Francisco de Vitoria
- Multisports pavilion :
 - 9,000 sq meters (96,875 Sq feet)
 - Completed in 2017 (Started in 2012)
 - Gymnasium & Pool
 - Office Spaces
- Designed by: Alberto Campo Baeza
- Structure by: Andres Rubio Moran




Background

- Simple Program
- Multi-purpose
- Volumetrically constrained to existing conditions
- Interconnected patio spaced between two “Clean buildings”
- Heavy focus on functionality



Main Structural System

- Rigid diaphragm system in accordance european building code standards.
- HEB Steel Flange Beams compose the gymnasium
- Cast in place concrete compiles the rigid frame of the office area.
- Precast Concrete Fiberglass panels installed as shear components on both diaphragms.




Ground Floor Plan

Gym
composes
more than
half of the
projected
building
footprint.


Ground Floor Plan

Gym
composes
more than
half of the
projected
building
footprint.




Gymnasium Background

- Multi-sports court area w/ seating
- Office spaces and locker rooms below
- Glazing, shear walls, column system
- Framed System
- 9 Structural Trusses
- Reinforced Fiberglass Concrete
- 2237.93 Meters Sq (24,088 Ft sq)
 - Length 58.60 Meters (192.25 feet)
 - Width 38.190 Meters (125 feet)
 - Height 11.95 Meters (39.20 feet)




Egress and “Offices”

- Offices, fitness rooms, and pool.
- Reinforced Concrete Framing
- Glazing, shear walls, column system
- Cast in place columns
- 524.88 Meters Sq * (5 Stories)
(5,649 Ft Sq)
 - Length 10.28 Meters (192.25 feet)
 - Width 47.6 Meters (125 feet)
 - Height 10.28 Meters (39.20 feet)




Gymnasium Foundation

- Isolation footings
- Shear wall footings
- 600mm exterior wall fiberglass concrete walls.




Office Foundation

- Consistent material usage from 5th floor to foundation plan.
- Isolated footings, and wall cast columns integral to project serviceability.




Visual Analysis

- Steel Framing vs. reinforced concrete diaphragm structures.



Connection Points

- Pin-connection points
- HEB double chord truss system.
- Rigid framing system
- Foundation connection via baseplates.
- Welded/Bolted Connections




Loading Diagram: Concrete

- Entire office portion : reinforced concrete systems
- Bear uniformly distributed flooring and roof systems.
- Columns vary in size: (30x35 / 60x90)
- Beams vary in size: typical beams (25x60) / deep beams (40x240)




Shear Diagram: Concrete

- Shear loading results for a typical uniformly distributed beam.




Moment Diagram: Concrete

- Bending moment follows suite, with grid spacing, and load placements.




Deflection Diagram: Concrete

- Exterior and interior shear, and stability components utilized to reinforce entire office portion superstructure.



Axial Reaction Diagram: Concrete


- Rigid connections
- Fixed supports




-

Framing System Short Sides


- HEB 180 Truss systems projected across roofing system.
- Diaphragm system is HEB 300 Beams and Girders.
- End Conditions, use HEB 180, and HEB 300s



Section Cut




North and South Ends




Loading Diagram: Truss

- Uniformly distributed load roof system, applied across entire roof, and distributed to both shear wall systems.




Shear Diagram: Truss

- HEB 180 webbing between double chords composed of HEB 300 spatial truss system.




Moment Diagram: Truss

- Bending possibly reduced with pretension stressing, and braced systems.




Deflection Diagram: Truss

- Left side wall projects straight to concrete floor column base plates, while right side component, projects forces into reinforced concrete framing system.




Axial Diagram: Truss

- 9 Spatial truss systems are braced bi-laterally.




Load Tracing System

- Exterior members are primary point of transfer from roof loading to foundation




Location Impacts

- NCSE-02, peak ground acceleration provided via the g chart, with higher values being at a higher risk.
- Winds procured from the west and southwest direction. And could create possibly vortex shedding





Summary

- General background information regarding site context
 - Wind patterns
 - Seismic hazard overview
 - Components of the structural system
 - Floor plan
 - location of structural components
 - Orientation and distribution of of the space in relation to structural components
 - Foundation
 - Visual Analysis
 - Material factor
 - Loading factor
 - Truss system analysis
 - Framing system
 - Load Tracing diagrams
- 

Summary

- General background information regarding site context
 - Wind patterns
 - Seismic hazard overview
- Components of the structural system
- Floor plan
 - location of structural components
 - Orientation and distribution of of the space in relation to structural components
 - Foundation
- Visual Analysis
 - Material factor
 - Loading factor
 - Truss system analysis
- Framing system
- Load Tracing diagrams



Summary

- General background information regarding site context
 - Wind patterns
 - Seismic hazard overview
- Components of the structural system
- Floor plan
 - location of structural components
 - Orientation and distribution of of the space in relation to structural components
 - Foundation
- Visual Analysis
 - Material factor
 - Loading factor
 - Truss system analysis
- Framing system
- Load Tracing diagrams



Summary

- General background information regarding site context
 - Wind patterns
 - Seismic hazard overview
- Components of the structural system
- Floor plan
 - location of structural components
 - Orientation and distribution of of the space in relation to structural components
 - Foundation
- Visual Analysis
 - Material factor
 - Loading factor
 - Truss system analysis
- Framing system
- Load Tracing diagrams





Axial Reaction Diagram: Concrete

- <https://www.flickr.com/photos/campobaeza/34042352774> = Background Photo
- <https://www.google.com/maps/place/Francisco+de+Vitoria+University+-+Madrid/@40.4403665,-3.8368576,766m/data=!3m2!1e3!4b1!4m5!3m4!1s0xd4185d02f8a6fe5:0x703d6f7e39d3e3aa!8m2!3d40.4403665!4d-3.8346689> - Google Maps References
- <https://archello.com/brand/andres-rubio-moran> - Background Photo Slide 3 (Truss placement)
- https://p-upload.facebook.com/deportesUFV/?ref=page_internal - Interior photo video pull
- <https://www.campobaeza.com/sports-pavilion-university/> - All remaining photos, documents, and diagrams
- <https://www.archdaily.com/875503/multi-sport-pavilion-and-classroom-complex-alberto-campo-baeza> - Research Pool
- Earthquake Code Permanent Commission of Spain (2002) Norma de Construcción Sismorresistente: Parte General y Edificación, NCSE-02. Ministry of Public Works of Spain, Madrid in Spanish Mezcuá, J., Rueda, J. & García Blanco, R.M. Nat Hazards (2011) 59: 1087. <https://doi.org/10.1007/s11069-011-9819-3> - Earthquake information
- <https://www.windfinder.com/forecast/madrid> - Wind loading information