

ARCH 331. Assignment #13

Date: 4/19/18, due 4/26/18

Pass-fail work

Problems: (none from Onouye & Kane)

- (37%) 13A) A solid one-way slab is to be used for a framing system of a one-way slab supported on beams on girders. Column spacing is 33 ft, with regularly spaced beams occurring at 11 ft center to center. (Assume the beams are 1 ft wide.) Superimposed dead load on the structure is 50 psf, and live load is 75 psf. Use $f'_c = 4$ ksi and $f_y = 60$ ksi; $\lambda = 1$. Determine the thickness for the slab and select the size and spacing for the positive and negative reinforcement to satisfy flexure requirements, and for the transverse reinforcement. Assuming there is proper bar spacing and cover, determine the minimum development lengths of the flexural reinforcement chosen. Also consider a 1 1/2 hour fire rating with a carbonate aggregate.

(frame analysis by coefficients, reinforced concrete slab design, development length)

Partial answers to check with: $V_{u-max} = 1.4$ k, $\phi V_c = 4.0$ k, $M_{u+end} = 1.8$ k-ft, $M_{u+mid} = 1.5$ k-ft, $M_{u-} = 2.1$ k-ft, $A_{temp-min} \approx 0.10$ in², $L_d = (14.25$ in. for a #3 for ex.)

- (7%) 13B) Size hollow core planks for the system and loads of problem 13A) when there are only beams at the columns (33 ft on center). Assume that the inverted T-beams the simply supported planks will be supported by are 1 ft wide in the stem. Choose the shallowest plank with the least reinforcement that will span the 32 feet while supporting the loads. Assume 2 in. of normal weight topping.

(floor span system design)

Partial answers to check with: estimated long term camber of 0.3 in.

- (14%) 13C) Select the minimum size square tied column and its reinforcement when the column has a dead load of 200 k, live load of 150 k, dead load bending moment of 100 k-ft, and live load bending moment of 100 k-ft. Also determine the axial capacity of the chosen column and reinforcement if ties are used. Assume $f'_c = 5$ ksi and $f_y = 60$ ksi.

(reinforced concrete column design aids)

Partial answers to check with: $e = 7$ in, $\phi P_n = 1078$ kips

- (12%) 13D) Select the minimum size round tied column and its reinforcement for the same load and bending moments of problem 13C). Also determine the axial capacity of the column and reinforcement chosen if spiral reinforcement is used. Assume $f'_c = 5$ ksi and $f_y = 60$ ksi.

(reinforced concrete column design aids)

Partial answers to check with: $\phi P_n = 1295$ kips

MORE NEXT PAGE

